


### **Specifications**

# **SMART Room System™**

with SMART Meeting Pro® software and one SMART Board® 8070i-G4 interactive flat panel Model SRS-MP-170

#### Overview


The SMART Room System™ with SMART Meeting Pro® software and one SMART Board® 8070i-G4 interactive flat panel features a 70" (178 cm) interactive flat panel, a camera, microphones, speakers and supporting hardware as well as SMART Meeting Pro software and SMART Meeting Pro PE software. This system is designed for use in highly collaborative team environments.




See smarttech.com for more information on this product.

# Dimensions and weights

#### **Dimensions**





	Weight	Shipping weight	Shipping dimensions
Interactive flat panel	205 lb. (93 kg)	251 lb. (114 kg)	771/8" × 561/4" × 153/8" (196 cm × 143 cm × 39 cm)
Wall mount	24 lb. (10.9 kg)	31 lb. (14 kg)	46" ×12 1/2" ×11" (117 cm × 32 cm × 28.1 cm)
Camera	8 oz. (0.2 kg)	2 lb. (0.9 kg)	15 5/8" × 5 1/2" × 4 3/8" (39.6 cm × 14 cm × 11 cm)
Table microphones and audio processor	2 lb. (0.9 kg)	6 lb. (2.5 kg)	161/2" × 97/8" × 7" (41.9 cm × 25.2 cm × 17.8 cm)
Speakers	15 lb. (7 kg)	20 lb. (9.1 kg)	37 3/4" × 15 1/2" × 7 3/8" (96 cm × 39.5 cm × 18.8 cm)
Cables and accessories	1 lb. (0.5 kg)	2 lb. 8 oz. (1.1 kg)	14" ×10 1/2" × 3 1/4" (35.6 cm × 26.7 cm × 8.3 cm)

<sup>\*</sup>All dimensions  $\pm$  1/8" (0.3 cm). All weights  $\pm$  2 lb. (0.9 kg).

#### Hardware

#### Included hardware

SBID 8070i-G4 SMART Board 8070i-G4 interactive flat panel

WM-SBID-501 Wall mount

CAM301 Camera

MIC500 Table microphone (×2)

MIX500 Audio processor

CSR500 Speakers

Included cables

For interactive flat 20' 8" (6.3 m) HDMI panel 4' (1.3 m) USB

16' 5" (5 m) USB extender

8' (2.4 m) IEC 60320 C13 to country-specific power

30' (9 m) audio (audio processor to microphone)

For camera 16' 5" (5 m) USB

Power

For table microphones

and audio processor 13' (4 m) audio (microphone to microphone)

16' 5" (5 m) USB

Power

For speakers 6' (1.8 m) dual RCA (audio processor to speaker)

16' 5" (5 m) audio (speaker to speaker)

Power

Interactive flat panel specifications

Touch technology DViT® (Digital Vision Touch) technology

Screen size (diagonal) 70" (178 cm)

Aspect ratio 16:9

Optimal resolution 1920 × 1080 at 60 Hz

Horizontal frequency 54–69.75 kHz (analog and digital)

Vertical frequency 48–62 Hz

Contrast ratio (typical) 4000:1

Brightness (typical) 180–250 cd/m<sup>2</sup>

Pixel pitch 0.807 mm

#### Camera specifications

Features Digital pan, tilt and zoom (DPTZ)

Automatic white balance

Automatic exposure and power line frequency detection

Manual lens tilt adjustment Internal privacy shutter Video recording indicator

30 frames per second (at  $\geq$  200 lx)

Aspect ratio 16:9

Resolution (maximum) 1920 × 1080

Field of view 109° (full)

98° (horizontal)

Depth of field 3'-33' (1-10 m)

Signal-to-noise ratio

Frame rate (typical)

(minimum)

33 dB at  $\ge$  50 lx 36 dB at  $\ge$  200 lx

Dynamic range (minimum)

42 dB

#### Table microphone specifications

Features Mute button and indicator

Daisy-chain up to five microphones

Local speaker audio

level

60-65 dBA measured at 20" (0.5 m)

#### Speaker specifications

Total harmonic

distortion

< 1% average < 3% maximum 80–10 kHz

Frequency response

± 6 dB, 80-10 kHz

Nominal volume

76 dBSPL

#### **Audio specifications**

Echo cancellation

> 45 dB at nominal receive output level

#### Software

Included software SMAR

SMART Meeting Pro software SMART Meeting Pro PE software

# Storage and operating requirements

#### Interactive flat panel power requirements and consumption

100-240V AC, 50-60 Hz Power requirements

Power consumption at 310 W

77°F (25°C)

# Other component power requirements and consumption

Camera 6 W (19V DC at 0.2A) Audi processor 20 W (19V DC at 0.06A) 58.5 W (19V DC at 0.585A) Speakers Total 84.5 W

Operating temperature 41-95°F (5-35°C)

Storage temperature -4-140°F (-20-60°C)

Humidity 5-80% relative humidity, non-condensing

# Certification and compliance

Regulatory certification UL (U.S. and Canada), FCC, IC, C-Tick, NOM, CU, CB, VCCI, KC, PSB and BIS

#### **Environmental compliance**

China EIP

European Union REACH, RoHS, WEEE, Battery, Packaging and ErP Standby

U.S. Packaging and Conflict Minerals

# Purchasing information

#### Order number

SRS-MP-170 SMART Room System with SMART Meeting Pro software and one SMART Board 8070i-G4

interactive flat panel

#### Optional accessories

MIC500 Additional table microphone

WSK-SINGLE Wall stand for transferring some of the weight of the interactive flat panel to the floor

#### Warranty

Two-year warranty Interactive flat panel

Camera

One-year warranty Speakers

Wall mount

90-day return Cables, pens, batteries and other items that can be purchased from the Store for SMART Parts

(see smarttech.com/Support/PartsStore)

**Extended warranty** 

EWY1-8070-SMP SMART Board 8070i-G4 interactive flat panel one-year warranty extension

LCD pixel policy See knowledgebase.force.com/articles/TROUBLESHOOTING/Limited-pixel-warranty-for-

SMART-Board-8000i-series-interactive-flat-panels

smarttech.com/support smarttech.com/contactsupport

© 2014 SMART Technologies ULC. All rights reserved. SMART Room System, SMART Meeting Pro, SMART Board, DViT, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patents. www.smarttech.com/patents. Contents are subject to change without notice. 06/2014.